

# SANSTICK 140S

## STICK Arc Welding

Processes  
STICK/L-TIG

Product Number  
IDU-W140S-U1DV

Input Voltage  
120/208-240 VAC 1 Phase  
Rated Output  
140A @ 15% Duty Cycle (120V)  
140A @ 25% Duty Cycle (240V)

Output Range  
5–140A Max  
Input Frequency  
50/60 Hz.  
Weight  
9.9lbs (4.5kg)

The SanRex 140S is a dual-voltage, DC STICK with L-TIG welding power supply.

### Features:

- **Exceptional Performance:** Delivering perfectly smooth, stable arc characteristics.
- **Lift Start TIG:** Provides TIG arc starting without use of High Frequency.
- **Auto Switch:** Multi-voltage 120/208-240 vac, single phase.
- **Certifications:** CSA, IEC-974
- **Thermal Overload Protection:** Indicator alerts the operator if duty cycle is exceeded or air-flow is blocked.
- **Cable and Plug Fitted:** Supplied with primary cable and plug. Includes adaptor for easy connection to 120/240vac receptacles.
- **Stick Package:** 140S comes complete with power supply, STICK kit and carry case.

**Compact and Portable  
DC Welding Inverter**



**1 Year Warranty**

## Ordering Information

Product	Part Number	Description
SANSTICK 140S Pkg.	IDU-W140S-U1DV	Includes 140S Power Supply, 8ft. Work Lead and Electrode Holder, 120/240 vac adaptor and Carry Case.

### Accessories

Work Lead	WCG0002	200Amp 8ft. Cable with Ground clamp (Included in package).
Electrode Lead	WCG0001	200 Amp 8ft. Cable and electrode holder (Included in package).
Adaptor	MS1012	120/240 vac Adaptor (Included in package).
TIG Torch	TK1019	18ft. (5.5m) 150 Amp 17 Style w/Gas Valve.
Carry Case	CC0001	Black Carry Case with Handle (Included in package).

**SanRex**

Customer Care  
Tel: 516-625-1313  
Fax: 516-625-8845

SANREX CORPORATION  
PORT WASHINGTON, NY, USA

www.sanrex.com  
SANSTICK 140S  
Form No.:102818140S